

TESLA TA36FFLL-1232IA



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), I FEEL function

Capacity			12000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	3500(1400-3520) 3500(1100-3750)	
Power input		W	997(450-1500) 970(400-1350)	
Current input		A	4.33(2.0-7.5) 4.3(1.6-7.0)	
SEER-SCOP/ Energy Class		W/W	6.17/A++ 4.06/A+	
Operating range (°C)			14 - 43°C -15 - 30°C	
Dehumidifying		Kg/h	1.1	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1800	
Max. current		A	8.5	
Compressor		Model	ASK103D53UFZE	
		Type	DC	
		Brand	GMCC	
Indoor	Fan motor	Model	YYK18-4B	
		Power input	W	18
		Capacity	uF	1.5
		Indoor Fan Speed RPM	r/min	1250
	Indoor fan	Dia. / Length	mm	ø97.8 / 558
	Indoor Air Circulation (m³/h)		m³/h	480
	Indoor Noise Level dB		dB(A)	33/29/27/24
	Net Dimension (LxWxH)		mm	727x285x195
	Packing Dimension (LxWxH)		mm	815x345x275
	Net Weight/Gross Weight		Kg	7,8/9,3
Outdoor	Fan motor	Model	YDK25-6B	
		Power input	W	25
		Capacity	uF	1.5
		Outdoor Fan Speed RPM	r/min	820
	Outdoor fan	Length	mm	390
	Outdoor Noise Level dB		dB(A)	52
	Net Dimension (LxWxH)		mm	815x340x540
	Packing Dimension (LxWxH)		mm	845x355x600
	Net Weight/Gross Weight		Kg	27,8/30,4
	Refrigerant type/weight		g	R32/710
Max. Discharge/Max. Suction pressure		Mpa	4/1	
Refrigerant piping	Liquid side / Gas side	mm	φ6.35(0,5) / φ9.52(0,6)	
	Max. refrigerant pipe length / Max. difference in level	m	18/6	